

SAFETY DATA SHEET

CORTEVA AGRISCIENCE FRANCE S.A.S.

Product name: STARANE™ 20 EC

Issue Date: 08/04/2021

Print Date: 08/04/2021

CORTEVA AGRISCIENCE FRANCE S.A.S. encourages you and expects you to read and understand the entire SDS as there is important information throughout the document. This SDS provides users with information relating to the protection of human health and safety at the workplace, protection of the environment and supports emergency response. Product users and applicators should primarily refer to the product label attached to or accompanying the product container.

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: STARANE™ 20 EC

Recommended use of the chemical and restrictions on use

Identified uses: Plant Protection Product Herbicide

COMPANY IDENTIFICATION

CORTEVA AGRISCIENCE FRANCE S.A.S.
1 bis avenue du 8 mai 1945 - Bâtiment Equinoxe II
78280 Guyancourt
FRANCE

Customer Information Number : +33 1 30 23 13 13
E-mail address : SDS@corteva.com

EMERGENCY TELEPHONE

24-Hour Emergency Contact : +44 161 88 41235
Local Emergency Contact : +44 161 88 41235

2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

Flammable liquids - Category 3 - H226
Aspiration hazard - Category 1 - H304
Skin irritation - Category 2 - H315
Skin sensitization - Sub-category 1B - H317
Eye irritation - Category 2 - H319
Specific target organ toxicity - single exposure - Category 3 - H335
Specific target organ toxicity - single exposure - Category 3 - H336
Short-term (acute) aquatic hazard - Category 1 - H400
Long-term (chronic) aquatic hazard - Category 1 - H410
For the full text of the H-Statements mentioned in this Section, see Section 16.

Label elements

Hazard pictograms



Signal Word: DANGER

Hazard statements

H226 Flammable liquid and vapor.
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
 P305 + P351 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P331 Do NOT induce vomiting.
 P501 Dispose of contents/container in accordance with applicable regulations.

Supplemental information

EUH401 To avoid risks to human health and the environment, comply with the instructions for use.

Contains Solvent naphtha (petroleum), light aromatic; 1,2,4-Trimethylbenzene; 1,3,5-Trimethylbenzene; Hexanol

Other hazards

No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

This product is a mixture.

CASRN / EC-No. / Index-No.	Concentration	Component	Classification
CASRN 81406-37-3 EC-No. 279-752-9 Index-No.	30.6%	Fluroxypyr 1-methylheptyl ester	Aquatic Acute - 1 - H400 Aquatic Chronic - 1 - H410

607-272-00-5			
CASRN 64742-95-6 EC-No. 265-199-0 Index-No. 649-356-00-4	>= 60.0 - < 70.0 %	Solvent naphtha (petroleum), light aromatic	Flam. Liq. - 3 - H226 STOT SE - 3 - H336 STOT SE - 3 - H335 Asp. Tox. - 1 - H304 Aquatic Chronic - 2 - H411
CASRN 95-63-6 EC-No. 202-436-9 Index-No. 601-043-00-3	>= 10.0 - < 20.0 %	1,2,4-Trimethylbenzene	Flam. Liq. - 3 - H226 Acute Tox. - 4 - H332 Skin Irrit. - 2 - H315 Eye Irrit. - 2 - H319 STOT SE - 3 - H335 Aquatic Chronic - 2 - H411
CASRN 108-67-8 EC-No. 203-604-4 Index-No. 601-025-00-5	>= 3.0 - < 10.0 %	1,3,5-Trimethylbenzene	Flam. Liq. - 3 - H226 Skin Irrit. - 2 - H315 Eye Irrit. - 2 - H319 STOT SE - 3 - H335 Asp. Tox. - 1 - H304 Aquatic Chronic - 2 - H411
CASRN 98-82-8 EC-No. 202-704-5 Index-No. 601-024-00-X	>= 2.5 - < 3.0 %	Cumene	Flam. Liq. - 3 - H226 STOT SE - 3 - H335 Asp. Tox. - 1 - H304 Aquatic Chronic - 3 - H412
CASRN 68953-96-8 EC-No. 273-234-6 Index-No. -	>= 1.0 - < 2.5 %	Benzenesulfonic acid, mono- C11-13-branched alkyl derivs., calcium salts	Acute Tox. - 4 - H312 Skin Irrit. - 2 - H315 Eye Dam. - 1 - H318 Aquatic Chronic - 2 - H411
CASRN 111-27-3 EC-No. 203-852-3 Index-No. 603-059-00-6	>= 1.0 - < 3.0 %	Hexanol	Flam. Liq. - 3 - H226 Acute Tox. - 4 - H302 Eye Irrit. - 2 - H319 STOT SE - 3 - H336
CASRN 1189173-42-9 EC-No. 918-811-1 Index-No. -	>= 1.0 - < 2.5 %	Hydrocarbons, C10, aromatics, <1% naphthalene	STOT SE - 3 - H336 Asp. Tox. - 1 - H304 Aquatic Chronic - 2 - H411

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

Description of first aid measures

General advice: First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air. If person is not breathing, call an emergency responder or ambulance, then give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask etc). Call a poison control center or doctor for treatment advice. If breathing is difficult, oxygen should be administered by qualified personnel.

Skin contact: Take off contaminated clothing. Wash skin with soap and plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice. Wash clothing before reuse. Shoes and other leather items which cannot be decontaminated should be disposed of properly.

Eye contact: Hold eyes open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eyes. Call a poison control center or doctor for treatment advice. Suitable emergency eye wash facility should be available in work area.

Ingestion: Immediately call a poison control center or doctor. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: Maintain adequate ventilation and oxygenation of the patient. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. The decision of whether to induce vomiting or not should be made by a physician. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Have the Safety Data Sheet, and if available, the product container or label with you when calling a poison control center or doctor, or going for treatment. Skin contact may aggravate preexisting dermatitis.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media: Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

Unsuitable extinguishing media: No data available

Special hazards arising from the substance or mixture

Hazardous combustion products: During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide. Hydrogen fluoride.

Unusual Fire and Explosion Hazards: Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids. Dense smoke is produced when product burns.

Advice for firefighters

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Consider feasibility of a controlled burn to minimize environment damage. Foam fire extinguishing system is preferred because uncontrolled water can spread possible contamination. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Burning liquids may be extinguished by dilution with water. Do not use direct water stream. May spread fire. Eliminate ignition sources. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage. Review the "Accidental Release Measures" and the "Ecological Information" sections of this (M)SDS.

Special protective equipment for firefighters: Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location. For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Isolate area. Keep unnecessary and unprotected personnel from entering the area. Keep upwind of spill. Ventilate area of leak or spill. No smoking in area. Eliminate all sources of ignition in vicinity of spill or released vapor to avoid fire or explosion. Vapor explosion hazard. Keep out of sewers. Refer to section 7, Handling, for additional precautionary measures. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Environmental precautions: Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. Spills or discharge to natural waterways is likely to kill aquatic organisms.

Methods and materials for containment and cleaning up: Contain spilled material if possible. Pump with explosion-proof equipment. If available, use foam to smother or suppress. Small spills: Absorb with materials such as: Clay. Dirt. Sand. Sweep up. Collect in suitable and properly labeled containers. Large spills: Contact the company for clean-up assistance. See Section 13, Disposal Considerations, for additional information.

7. HANDLING AND STORAGE

Precautions for safe handling: Keep out of reach of children. Keep away from heat, sparks and flame. Do not swallow. Avoid breathing vapor or mist. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated contact with skin. Wash thoroughly after handling. Keep container closed. Use with adequate ventilation. No smoking, open flames or sources of ignition in handling and storage area. Electrically ground and bond all equipment. Use of non-sparking or explosion-proof equipment may be necessary, depending upon the type of operation. Containers, even those that have been emptied, can contain vapors. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Conditions for safe storage, including any incompatibilities: Minimize sources of ignition, such as static build-up, heat, spark or flame. Store in a dry place. Store in original container. Keep container tightly closed when not in use. Do not store near food, foodstuffs, drugs or potable water supplies.

Storage stability: To maintain product quality, recommended storage temperature is 0 °C

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value/Notation
Solvent naphtha (petroleum), light aromatic	ACGIH	TWA	200 mg/m ³ , total hydrocarbon vapor
	Dow IHG	TWA	100 mg/m ³
	Dow IHG	STEL	300 mg/m ³
Fluroxypyr 1-methylheptyl ester	Dow IHG	TWA	10 mg/m ³
1,2,4-Trimethylbenzene	ACGIH	TWA	25 ppm
	2000/39/EC	TWA	100 mg/m ³ 20 ppm
1,3,5-Trimethylbenzene	ACGIH	TWA	25 ppm
	2000/39/EC	TWA	100 mg/m ³ 20 ppm
Cumene	ACGIH	TWA	50 ppm
	2000/39/EC	TWA	100 mg/m ³ 20 ppm
	2000/39/EC	TWA	SKIN
	2000/39/EC	STEL	250 mg/m ³ 50 ppm
	2000/39/EC	STEL	SKIN
	2019/1831/EU	TWA	50 mg/m ³ 10 ppm
	2019/1831/EU	STEL	250 mg/m ³ 50 ppm

RECOMMENDATIONS IN THIS SECTION ARE FOR MANUFACTURING, COMMERCIAL BLENDING AND PACKAGING WORKERS. APPLICATORS AND HANDLERS SHOULD SEE THE PRODUCT LABEL FOR PROPER PERSONAL PROTECTIVE EQUIPMENT AND CLOTHING.

Exposure controls

Engineering controls: Use engineering controls to maintain airborne level below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Use chemical goggles. Chemical goggles should be consistent with EN 166 or equivalent.

Skin protection

Hand protection: Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and micro-organisms. Examples of preferred glove barrier materials include: Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Styrene/butadiene rubber. Viton. Examples of acceptable glove barrier materials include: Butyl rubber. Chlorinated polyethylene. Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyvinyl chloride ("PVC" or "vinyl"). When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection

class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended. Glove thickness alone is not a good indicator of the level of protection a glove provides against a chemical substance as this level of protection is also highly dependent on the specific composition of the material that the glove is fabricated from. The thickness of the glove must, depending on model and type of material, generally be more than 0.35 mm to offer sufficient protection for prolonged and frequent contact with the substance. As an exception to this general rule it is known that multilayer laminate gloves may offer prolonged protection at thicknesses less than 0.35 mm. Other glove materials with a thickness of less than 0.35 mm may offer sufficient protection when only brief contact is expected. **NOTICE:** The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use an approved respirator. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of the material. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus. In confined or poorly ventilated areas, use an approved self-contained breathing apparatus or positive pressure air line with auxiliary self-contained air supply.

Use the following CE approved air-purifying respirator: Organic vapor cartridge with a particulate pre-filter, type AP2 (meeting standard EN 14387).

See SECTION 7: Handling and storage and SECTION 13: Disposal considerations for measures to prevent excessive environmental exposure during use and waste disposal.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state	Liquid.
Color	Brown
Odor	Aromatic
Odor Threshold	No test data available
pH	5.3 1% CIPAC MT 75.2 (1% aqueous suspension)
Melting point/range	Not applicable
Freezing point	No data available
Boiling point (760 mmHg)	No test data available
Flash point	closed cup 55 °C CIPAC MT 12
Evaporation Rate (Butyl Acetate = 1)	No test data available
Flammability (solid, gas)	Not Applicable
Lower explosion limit	No test data available
Upper explosion limit	No test data available
Vapor Pressure	No test data available

Relative Vapor Density (air = 1)	No test data available
Relative Density (water = 1)	No data available
Water solubility	emulsifiable
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	442 °C <i>EC Method A15</i>
Decomposition temperature	No test data available
Dynamic Viscosity	No test data available
Kinematic Viscosity	2.96 mm ² /s at 20 °C <i>ASTM D455</i>
Explosive properties	No No <i>EEC A14</i>
Oxidizing properties	No test data available
Liquid Density	0.9698 g/mL at 20 °C <i>Pyknometer</i>
Molecular weight	No data available
Surface tension	27.0 mN/m at 25 °C <i>EC Method A5</i>

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: No dangerous reaction known under conditions of normal use.

Chemical stability: Thermally stable at typical use temperatures.

Possibility of hazardous reactions: Polymerization will not occur.

Conditions to avoid: Exposure to elevated temperatures can cause product to decompose. Generation of gas during decomposition can cause pressure in closed systems. Avoid direct sunlight.

Incompatible materials: Avoid contact with: Strong acids. Strong bases. Strong oxidizers.

Hazardous decomposition products: Decomposition products depend upon temperature, air supply and the presence of other materials. Toxic gases are released during decomposition.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Acute toxicity

Acute oral toxicity

Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury.

As product:

LD50. Rat. male. > 2,000 - 3,500 mg/kg

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product:
LD50. Rat. male and female. > 5,000 mg/kg

Acute inhalation toxicity

Vapor concentrations are attainable which could be hazardous on single exposure. May cause respiratory irritation and central nervous system depression. Symptoms may include headache, dizziness and drowsiness, progressing to incoordination and unconsciousness.

As product: The LC50 has not been determined.

Skin corrosion/irritation

Brief contact may cause severe skin irritation with pain and local redness.
May cause drying and flaking of the skin.

Serious eye damage/eye irritation

May cause pain disproportionate to the level of irritation to eye tissues.
May cause moderate eye irritation.
May cause slight corneal injury.

Sensitization

Has caused allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:
No relevant data found.

Specific Target Organ Systemic Toxicity (Single Exposure)

May cause respiratory irritation.

May cause drowsiness or dizziness.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

For the active ingredient(s):
Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Based on information for component(s):
In animals, effects have been reported on the following organs:
Eye.
Gastrointestinal tract.
Respiratory tract.

Carcinogenicity

For the minor component(s): Has caused cancer in laboratory animals. However, the relevance of this to humans is unknown.

For the active ingredient(s): Did not cause cancer in laboratory animals.

Teratogenicity

For the active ingredient(s): Has been toxic to the fetus in laboratory animals at doses toxic to the mother. Did not cause birth defects in laboratory animals.

For the solvent(s): Has been toxic to the fetus in laboratory animals at doses toxic to the mother. Has caused birth defects in laboratory animals only at doses producing severe toxicity in the mother.

Reproductive toxicity

For the solvent(s): In laboratory animal studies, effects on reproduction have been seen only at doses that produced significant toxicity to the parent animals. In animal studies, active ingredient did not interfere with reproduction.

Mutagenicity

For the active ingredient(s): In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

Aspiration Hazard

May be fatal if swallowed and enters airways.

COMPONENTS INFLUENCING TOXICOLOGY:**Fluroxypyr 1-methylheptyl ester****Acute inhalation toxicity**

Prolonged exposure is not expected to cause adverse effects. Dust may cause irritation to upper respiratory tract (nose and throat).

Maximum attainable concentration. LC50. Rat. male and female. 4 Hour. dust/mist. > 1.16 mg/l No deaths occurred at this concentration.

Solvent naphtha (petroleum), light aromatic**Acute inhalation toxicity**

Vapor concentrations are attainable which could be hazardous on single exposure. May cause respiratory irritation and central nervous system depression. Symptoms may include headache, dizziness and drowsiness, progressing to incoordination and unconsciousness.

LC50. Rat. 4 Hour. vapour. > 10.2 mg/l

1,2,4-Trimethylbenzene**Acute inhalation toxicity**

Prolonged excessive exposure may cause serious adverse effects, even death. Excessive exposure may cause irritation to upper respiratory tract (nose and throat) and lungs. May cause central nervous system effects. Symptoms of excessive exposure may be anesthetic or narcotic effects; dizziness and drowsiness may be observed.

LC50. Rat. 4 Hour. vapour. 18 mg/l

1,3,5-Trimethylbenzene**Acute inhalation toxicity**

LC50. Rat. male and female. 4 Hour. vapour. > 10.2 mg/l No deaths occurred following exposure to a saturated atmosphere.

Cumene**Acute inhalation toxicity**

LC50. Rat. 4 Hour. vapour. > 17.6 mg/l No deaths occurred at this concentration.

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts**Acute inhalation toxicity**

The LC50 has not been determined.

Hexanol**Acute inhalation toxicity**

LC50. Rat. male and female. 1 Hour. vapour. > 21 mg/l No deaths occurred at this concentration.

Hydrocarbons, C10, aromatics, <1% naphthalene**Acute inhalation toxicity**

Prolonged excessive exposure may cause adverse effects. May cause central nervous system effects. Symptoms may include headache, dizziness and drowsiness, progressing to incoordination and unconsciousness. Excessive exposure may cause irritation to upper respiratory tract (nose and throat) and lungs.

As product: The LC50 has not been determined.

For similar material(s): LC50. Rat. 4 Hour. vapour. > 4.688 mg/l

Maximum attainable concentration.

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Toxicity**Acute toxicity to fish**

Material is very toxic to aquatic organisms (LC50/EC50/IC50 below 1 mg/L in the most sensitive species).

LC50. Oncorhynchus mykiss (rainbow trout). flow-through test. 96 Hour. 8.5 mg/l. OECD Test Guideline 203

Acute toxicity to aquatic invertebrates

EC50. Daphnia magna (Water flea). flow-through test. 48 Hour. 6.2 mg/l. OECD Test Guideline 202

Acute toxicity to algae/aquatic plants

ErC50. Pseudokirchneriella subcapitata (green algae). static test. 72 Hour. > 40 mg/l. OECD Test Guideline 201

ErC50. diatom Navicula sp.. Static. 72 Hour. 0.684 mg/l. OECD Test Guideline 201

Toxicity to Above Ground Organisms

Material is practically non-toxic to birds on an acute basis (LD50 > 2000 mg/kg).

oral LD50. Colinus virginianus (Bobwhite quail). mortality. > 2250mg/kg bodyweight.

contact LD50. Apis mellifera (bees). 48 Hour. mortality. > 100µg/bee

oral LD50. Apis mellifera (bees). 48 Hour. mortality. > 130µg/bee

Toxicity to soil-dwelling organisms

LC50. Eisenia fetida (earthworms). 14 d. survival. 270 mg/kg

Persistence and degradability**Fluroxypyr 1-methylheptyl ester**

Biodegradability: Material is not readily biodegradable according to OECD/EEC guidelines.
10-day Window: Fail
Biodegradation: 32 %
Exposure time: 28 d
Method: OECD Test Guideline 301D or Equivalent

Theoretical Oxygen Demand: 2.2 mg/mg

Stability in Water (1/2-life)
Hydrolysis. half-life. 454 d

Solvent naphtha (petroleum), light aromatic

Biodegradability: For the major component(s): Material is expected to biodegrade very slowly (in the environment). Fails to pass OECD/EEC tests for ready biodegradability. For some component(s): Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

1,2,4-Trimethylbenzene

Biodegradability: Material is ultimately biodegradable (reaches > 70% mineralization in OECD test(s) for inherent biodegradability).

Biodegradation: 100 %
Exposure time: 1 d

1,3,5-Trimethylbenzene

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

10-day Window: Not applicable
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 301C or Equivalent
10-day Window: Not applicable
Biodegradation: 50 %
Exposure time: 4.4 d
Method: Calculated.

Cumene

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.
10-day Window: Pass
Biodegradation: 70 %
Exposure time: 20 d
Method: OECD Test Guideline 301D or Equivalent

Photodegradation
Test Type: Half-life (indirect photolysis)
Sensitization: OH radicals
Atmospheric half-life: 1.55 d
Method: Estimated.

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts

Biodegradability: Material is expected to biodegrade very slowly (in the environment). Fails to pass OECD/EEC tests for ready biodegradability.

10-day Window: Fail

Biodegradation: 2.9 %

Exposure time: 28 d

Method: OECD Test Guideline 301E or Equivalent

Hexanol

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Pass

Biodegradation: 61 %

Exposure time: 30 d

Method: OECD Test Guideline 301D or Equivalent

10-day Window: Pass

Biodegradation: 77 %

Exposure time: 30 d

Method: OECD Test Guideline 301D or Equivalent

Hydrocarbons, C10, aromatics, <1% naphthalene

Biodegradability: Material is inherently biodegradable (reaches > 20% biodegradation in OECD test(s) for inherent biodegradability).

Bioaccumulative potential

Fluroxypyr 1-methylheptyl ester

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 5.04 Measured

Bioconcentration factor (BCF): 26 Oncorhynchus mykiss (rainbow trout) Measured

Solvent naphtha (petroleum), light aromatic

Bioaccumulation: For the major component(s): Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5). For the minor component(s): Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

1,2,4-Trimethylbenzene

Bioaccumulation: Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).

Partition coefficient: n-octanol/water(log Pow): 3.63 Measured

Bioconcentration factor (BCF): 33 - 275 Cyprinus carpio (Carp) 56 d Measured

1,3,5-Trimethylbenzene

Bioaccumulation: Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).

Partition coefficient: n-octanol/water(log Pow): 3.42 Measured

Bioconcentration factor (BCF): 161 Pimephales promelas (fathead minnow) Measured

Cumene

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 3.4 - 3.7 Measured

Bioconcentration factor (BCF): 35.5 Fish Measured

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts

Bioaccumulation: Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).

Partition coefficient: n-octanol/water(log Pow): 4.6 OECD Test Guideline 107 or Equivalent

Hexanol

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): 1.8 Measured

Hydrocarbons, C10, aromatics, <1% naphthalene

Bioaccumulation: No data available for this product. For similar material(s): Bioconcentration potential is high (BCF > 3000 or Log Pow between 5 and 7).

Mobility in soil

Fluroxypyr 1-methylheptyl ester

Expected to be relatively immobile in soil (Koc > 5000).

Partition coefficient (Koc): 6200 - 43000

Solvent naphtha (petroleum), light aromatic

For the major component(s):

Potential for mobility in soil is low (Koc between 500 and 2000).

1,2,4-Trimethylbenzene

Potential for mobility in soil is low (Koc between 500 and 2000).

Partition coefficient (Koc): 720 Estimated.

1,3,5-Trimethylbenzene

Potential for mobility in soil is low (Koc between 500 and 2000).

Partition coefficient (Koc): 741.65 Estimated.

Cumene

Potential for mobility in soil is low (Koc between 500 and 2000).

Partition coefficient (Koc): 800 - 2800 Estimated.

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts

No relevant data found.

Hexanol

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient (Koc): 8.3

Hydrocarbons, C10, aromatics, <1% naphthalene

No relevant data found.

Results of PBT and vPvB assessment

Fluroxypyr 1-methylheptyl ester

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

Solvent naphtha (petroleum), light aromatic

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

1,2,4-Trimethylbenzene

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

1,3,5-Trimethylbenzene

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

Cumene

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

Hexanol

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

Hydrocarbons, C10, aromatics, <1% naphthalene

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

Other adverse effects**Fluroxypyr 1-methylheptyl ester**

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Solvent naphtha (petroleum), light aromatic

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

1,2,4-Trimethylbenzene

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

1,3,5-Trimethylbenzene

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Cumene

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Benzenesulfonic acid, mono-C11-13-branched alkyl derivs., calcium salts

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Hexanol

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

Hydrocarbons, C10, aromatics, <1% naphthalene

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

13. DISPOSAL CONSIDERATIONS

Disposal methods:

If wastes and/or containers cannot be disposed of according to the product label directions, disposal of this material must be in accordance with your local or area regulatory authorities. This information presented below only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations. If the material as supplied becomes a waste, follow all applicable regional, national and local laws.

The definitive assignment of this material to the appropriate EWC group and thus its proper EWC code will depend on the use that is made of this material. Contact the authorized waste disposal services.

14. TRANSPORT INFORMATION

Classification for ROAD and Rail transport:

Proper shipping name	FLAMMABLE LIQUID, N.O.S.(Aromatic hydrocarbon)
UN number	UN 1993
Class	3
Packing group	III
Environmental hazards	Fluroxypyr 1-methylheptyl ester

Classification for SEA transport (IMO-IMDG):

Proper shipping name	FLAMMABLE LIQUID, N.O.S.(Aromatic hydrocarbon)
UN number	UN 1993
Class	3
Packing group	III
Marine pollutant	Fluroxypyr 1-methylheptyl ester
Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code	Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Proper shipping name	Flammable liquid, n.o.s.(Aromatic hydrocarbon)
UN number	UN 1993
Class	3
Packing group	III

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Listed in Regulation: FLAMMABLE LIQUIDS

Number in Regulation: P5c

5,000 t

50,000 t

Listed in Regulation: ENVIRONMENTAL HAZARDS

Number in Regulation: E1

100 t

200 t

Listed in Regulation: Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Number in Regulation: 34

2,500 t

25,000 t

Classification and labeling have been performed according to Regulation (EC) No 1272/2008.

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

H226	Flammable liquid and vapor.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Revision

Identification Number: 278745 / Issue Date: 08/04/2021 / Version: 1.2

DAS Code: EF-1512

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

2000/39/EC	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2019/1831/EU	Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
ACGIH	USA. ACGIH Threshold Limit Values (TLV)
Dow IHG	Dow Industrial Hygiene Guideline

SKIN	Absorbed via skin
STEL	Short term exposure limit
TWA	Limit Value - eight hours
Acute Tox.	Acute toxicity
Aquatic Acute	Short-term (acute) aquatic hazard
Aquatic Chronic	Long-term (chronic) aquatic hazard
Asp. Tox.	Aspiration hazard
Eye Dam.	Serious eye damage
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquids
Skin Irrit.	Skin irritation
STOT SE	Specific target organ toxicity - single exposure

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

CORTEVA AGRISCIENCE FRANCE S.A.S. urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown

above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

IL